



MODEL	WCFS 25
L =	600

**SECTION A-A** Dim is subject to model will be confirmed from factory

TECHNICAL DATA		WCFS 25
a)	EXTERNAL DIM. (W x D x H)	1680 x (610+600) x 1070
b)	TEMPERATURE RANGE / CONTROLLER (s)	3°C to 5°C / XR 20C
c)	REFRIGERANT / CONTROL DEVICE	R-404a / Capillary tube
d)	COOLING CAPACITY (Btu.)	2208
e)	COMPRESSOR (Hp.)	1/3
f)	BAY TO ACCOMODATE G/N PAN 1/1	(Bay size accomodate 5 Pan)
g)	INTERIOR LIGHT (W.) , [Fluo]	58x1
h)	VOLTAGE SUPPLY. / Hz. / Ph.	220V. / 50 Hz. / 1 Ph
	AMPERAGE	3
i)	BODY & BOTTOM	PUR injection : external cover sheet 19 ga.(1.0 mm.) s/s # 4, 2-b finishing,(or as specified.) Internal cover sheet 22 ga. s/s 304 mirrorlike polished surface.
	SIDE PANELS	Double glazed, condenstop glass
	SKELETON	Angle steel bar 1-1/2" 6mmt.
	FRONT SLANT GLASS	Double glazed, condenstop glass
	DOOR STRUCTURE	Sliding type
	FURNISHING	Door leave(s) is internally filmed with mirrorlike film faced to front.
j)	DEFROST SYSTEM	Air defrost
k)	CONDENSATE WATER VAPORIZING SYSTEM	Use waste heat from compressor
l)	OPTION	(a) GN pan 1/1 x 65 mmd.

**NOTE :**  
**S/S # 4 FINISHED**  
**↔ REFERS TO**  
**S/S GRAIN DIRECTION**  
**(HORIZONTAL)**

<b>WELBILT</b> Manufacturing(Thailand)Ltd.	UNLESS OTHERWISE NOTED	PROJECT: <b>STODDART OEM - WOODSON COLD FOOD DISPLAY</b>	P/O NO.
	DESIGN DIMENSIONS ARE IN mm.	PRODUCT: <b>AS ABOVE SPECIFIED</b>	QTY.
SCALE <b>NTS.</b>	DWG. NO. <b>WCFS 25</b>	JOB NO.	DATE: <b>11/10/07</b>
SA1:	PAGE NO.	ITEM:	REVISION: <b>H</b>
SA2:	PAGE NO.	DRAWN:	CHECKED:
	SA1:	SA2:	APPROVED:
	SA1:	SA2:	AA: